

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
26 February 2004 (26.02.2004)

PCT

(10) International Publication Number
WO 2004/017372 A2

(51) International Patent Classification⁷:

H01L

(74) Agents: CARLSON, Judith, L. et al.; Honeywell International, Inc., Law Department AB2, P. O. Box 2245, Morristown, NJ 07962-9806 (US).

(21) International Application Number:

PCT/US2003/025461

(22) International Filing Date: 14 August 2003 (14.08.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/403,302 14 August 2002 (14.08.2002) US

(71) Applicant (for all designated States except US): HONEYWELL INTERNATIONAL, INC. [US/US]; a Corporation of the State of Delaware, Law Department AB2, P.O. Box 2245, Morristown, NJ 07962-9806 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): RICHEY, Manuel, F. [US/US]; 29005 Orchard Road, Paola, KS 66071 (US). REIM, Terry, Kenneth [US/US]; 206 West Nichols, Spring Hill, KS 66083 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR REDUCING ELECTROMAGNETIC EMISSIONS FROM ELECTRONIC CIRCUITS



WO 2004/017372 A2

(57) Abstract: An electronic circuit (10) comprising at least one electrical component (12) and at least one grounding point (16) is provided that includes a first layer of non-conductive coating (18) and a second layer of conductive coating (20). The non-conductive coating (18) is applied over the electrical component (12) in such a manner that the grounding point (16) remains uncoated. The conductive coating (20) is applied over the non-conductive coating (18) and the grounding point (16) so as to ground the conductive coating (20). The conductive coating (20) thus shields the electrical component (12) to thereby reduce electromagnetic emissions from the electronic circuit (10). Various exemplary embodiments of the coated electronic circuit and associated method are provided.



Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.